

## EZ-Clean™ Scale Terminal Systems

### NEMA 4X Packaged Scale Terminal For Hose-down Applications

Feature	Description																
Physical Dimensions (W x H x D)	Typical Flush-Mount Enclosure Sizes (Based on Requested Options)																
	<table border="1"> <thead> <tr> <th>Terminal</th> <th>Height*</th> <th>Width*</th> <th>Depth</th> </tr> </thead> <tbody> <tr> <td>JAGXTREME®</td> <td>19" (483mm)</td> <td>16" (406mm)</td> <td>6" (152mm)</td> </tr> <tr> <td>LYNX®/PANTHER®</td> <td>12" (305mm)</td> <td>16" (406mm)</td> <td>6" (152mm)</td> </tr> <tr> <td>PUMA®</td> <td>22" (559mm)</td> <td>16" (406mm)</td> <td>10" (254mm)</td> </tr> </tbody> </table>	Terminal	Height*	Width*	Depth	JAGXTREME®	19" (483mm)	16" (406mm)	6" (152mm)	LYNX®/PANTHER®	12" (305mm)	16" (406mm)	6" (152mm)	PUMA®	22" (559mm)	16" (406mm)	10" (254mm)
	Terminal	Height*	Width*	Depth													
	JAGXTREME®	19" (483mm)	16" (406mm)	6" (152mm)													
	LYNX®/PANTHER®	12" (305mm)	16" (406mm)	6" (152mm)													
PUMA®	22" (559mm)	16" (406mm)	10" (254mm)														
* wall mounting flange increases overall height and width by 3"																	
note: Wall mount enclosure with EZ-Clean™ controls optionally available																	
Operating Temperature	-10°C to 40°C (14°F to 104°F) typical, dependent upon requested options																
Power	120 VAC or 240 VAC, 47-63 Hz, order specific																
Available Terminals	JAGXTREME, LYNX, PANTHER, PUMA																
Required Air Pressure	100 psi (6.7 bar)																
Supply Port Size	1/4" NPT																
Mounting	Flush mount into wall, mount onto wall, or onto optional pedestal (order specific)																
Options (Factory-configured)	<ul style="list-style-type: none"> <li>• METTLER TOLEDO's superior JAGXTREME® analog or POWERCELL® scale interface technologies with optional PLC interface cards. Other METTLER TOLEDO scale terminals also supported</li> <li>• Optional multiple scale terminals in one enclosure</li> </ul>																
Scale Interface																	
I/O Modules	<ul style="list-style-type: none"> <li>• 120 VAC or 240V AC I/O Modules</li> </ul>																
Scale Pneumatic Lift Controls	<ul style="list-style-type: none"> <li>• Air supply fittings, pressure regulator, and internal or external key-lock manual switch for raising and lowering VERTEX® EZ-Clean scale</li> </ul>																
Intrinsic Safe Barriers	<ul style="list-style-type: none"> <li>• ISB15000 barrier for analog 5 to 15 volt load cells</li> <li>• CMOS barrier for METTLER TOLEDO POWERCELL®</li> </ul>																
Printer	<ul style="list-style-type: none"> <li>• Thermal printer with wash down hood</li> </ul>																
Lights/Buttons/Switches	<ul style="list-style-type: none"> <li>• Per customer requirements</li> </ul>																

Integrates with  
**VERTEX®**  
**2158 EZ-Clean™**  
**Scale**



Features	Benefits
Compact 6" overall depth	<ul style="list-style-type: none"> <li>• Allows for easy flush mounting into building wall</li> </ul>
Optional integrated pneumatic controls	<ul style="list-style-type: none"> <li>• Allows user to easily access scale lift controls</li> <li>• Control options include internal or external key-lock providing user flexibility</li> </ul>
Brushed stainless steel fuse welded faceplate with minimal seams	<ul style="list-style-type: none"> <li>• Excellent performance in "hose-down" applications where crevices and openings must be minimized to prevent fungal/bacteria growth</li> </ul>
Compact, integrated design	<ul style="list-style-type: none"> <li>• Less space required</li> <li>• Aesthetically pleasing</li> <li>• Optional shallow mount version for 4" wall depth</li> </ul>
Heavy duty, NEMA 4, dual latches	<ul style="list-style-type: none"> <li>• Provides rugged, tamper resistant, reliable door seal</li> </ul>
Multiple Terminal Options	<ul style="list-style-type: none"> <li>• Provides ability to select terminal best suited for application</li> </ul>

Produced in a facility that is



Specifications subject to change without notice.  
©2004 Mettler-Toledo, Inc.  
METTLER TOLEDO® and JAGXTREME® are registered trademarks of Mettler-Toledo, Inc.

Contact your local authorized METTLER TOLEDO distributor or sales office for further information.

**17083200A**